PKCELL®
Green energy, easy life



RECHARGEABLE BATTERY&CHARGER

Open the era of new energy technology

Shenzhen PKCELL Battery Co LTD is one of largest battery mafac turing enterprises in China for its biggest production ...

www.pkcell.com
www.pkcell.net

NiMH Rechargeable battery

PKCELL Ni-MH Rechargeable batteries offer high capacity performance, produce less waste than disposable batteris & enable energy and raw material savings.Good for all applications: Digital camera, portable video, game, flashlight, remote control, toy, MP3/MP4 player, electric razor.





Ni-MH
Consumer Rechargeable Battery
(CE ROHS certificates)






Ni-MH
Already Charged Ready For Use






Ni-Zn Battery





Ni-MH Rechargeable Battery (CE,ROHS certificates)



Type	Model	Size	Dimension (max) Diameter (mm)	Dimension (max) Height (mm)	Capacity (mAH)	Nominal Voltage(V)	Standard Charge Current (mA)	Standard Charge Time (H)	Rapid Charge Current (mA)	Rapid Charge Time (H)	Reference Weight
AAAA	AAAA250	AAAA	8.1	38.1	250	1.2	25	15	250	1.2	7
AAA	1/4AAA80	1/4AAA	10.5	11.5	80	1.2	8	15	80	1.2	5
	1/3AAA150	1/3AAA	10.5	17	150	1.2	15	15	150	1.2	6.2
	2/3AAA300	2/3AAA	10.5	29	300	1.2	30	15	300	1.2	8.5
	AAA600A/B	AAA	10.5	44.5/43	600	1.2	60	15	600	1.2	12
	AAA700A/B	AAA	10.5	44.5/43	700	1.2	70	15	350	2.4	12.5
	AAA800A	AAA	10.5	44.5	800	1.2	80	15	240	4	13
	AAA900A	AAA	10.5	44.5	900	1.2	90	15	270	4	13.5
	AAA1000A	AAA	10.5	44.5	1000	1.2	100	15	300	4	14
AA	1/3AA350	1/3AA	14.5	17	350	1.2	35	15	350	1.2	8
	2/3AA700	2/3AA	14.5	29	700	1.2	70	15	700	1.2	15
	4/5AA1300	4/5AA	14.5	43	1300	1.2	130	15	1300	1.2	23
	AA600A	AA	14.5	50.5	600	1.2	60	15	600	1.2	19
	AA700A	AA	14.5	50.5	700	1.2	70	15	700	1.2	20
	AA800A	AA	14.5	50.5	800	1.2	80	15	800	1.2	21
	AA1000A	AA	14.5	50.5	1000	1.2	100	15	1000	1.2	22
	AA1200A/B	AA	14.5	50.5/49	1200	1.2	120	15	1200	1.2	25
	AA1300A/B	AA	14.5	50.5/49	1300	1.2	130	15	1300	1.2	26
	AA1500A/B	AA	14.5	50.5/49	1500	1.2	150	15	1500	1.2	27
	AA1600A/B	AA	14.5	50.5/49	1600	1.2	160	15	1600	1.2	27
	AA1700A/B	AA	14.5	50.5/49	1700	1.2	170	15	1700	1.2	28
	AA1800A/B	AA	14.5	50.5/49	1800	1.2	180	15	900	2.4	29
	AA2000A/B	AA	14.5	50.5/49	2000	1.2	200	15	1000	2.4	30
	AA2100A	AA	14.5	50.5	2100	1.2	210	15	630	4	30
	AA2200A	AA	14.5	50.5	2200	1.2	220	15	660	4	31
	AA2300A	AA	14.5	50.5	2300	1.2	230	15	690	4	31
	AA2400A	AA	14.5	50.5	2400	1.2	240	15	720	4	31.6
	AA2500A	AA	14.5	50.5	2500	1.2	250	15	750	4	31.6
	AA2600A	AA	14.5	50.5	2600	1.2	260	15	780	4	33
A	A1800	A	17	50	1800	1.2	180	15	1800	1.2	34
	A2100	A	17	50	2100	1.2	210	15	2100	1.2	35
	A2300	A	17	50	2300	1.2	230	15	2300	1.2	36
	4/3A3800	4/3A	17	67	3800	1.2	380	15	3800	1.2	52
18670	18670/4200	18670	18.5	67	4200	1.2	420	15	2100	2.4	63
	18670/4500	18670	18.5	67	4500	1.2	450	15	2100	2.4	66
SC	SC2500P	SC	23	43	2500	1.2	250	15	2500	1.2	58
	SC2500H	SC	23	43	2500	1.2	250	15			58
	SC3000	SC	23	43	3000	1.2	300	15	3000	1.2	60
	SC3300	SC	23	43	3300	1.2	330	15	3300	1.2	62
	SC3500	SC	23	43	3500	1.2	350	15	3500	1.2	64
	SC3600	SC	23	43	3600	1.2	360	15	3600	1.2	65.5
C	C1500A	C	25.8	51	1500	1.2	150	15	1500	1.2	42
	C3000A/B	C	25.8	51/50	3000	1.2	300	15	3000	1.2	70
	C3500A/B	C	25.8	51/50	3500	1.2	350	15	3500	1.2	73
	C4500A	C	25.8	51	4500	1.2	450	15	2250	2.4	85
D	D3000A	D	33	61.5	3000	1.2	300	15	3000	1.2	81
	D7000B	D	33	60.5	7000	1.2	700	15	7000	1.2	145
	D8000A	D	33	61.5	8000	1.2	800	15	8000	1.2	155
	D9000A	D	33	61.5	9000	1.2	900	15	4500	2.4	160
F	F12000	F	33	90.5	12000	1.2	1200	15	6000	2.4	225
	F13000	F	33	90.5	13000	1.2	1300	15	6500	2.4	235
9V	9V 160	9V	17.5(T)*26.5(W)*48.5(H)		160	1.2	16	15	160	1.2	42
	9V 200	9V	17.5(T)*26.5(W)*48.5(H)		200	1.2	20	15	200	1.2	45
	9V 250	9V	17.5(T)*26.5(W)*48.5(H)		250	1.2	25	15	250	1.2	47
	9V 300	9V	17.5(T)*26.5(W)*48.5(H)		300	1.2	30	15	300	1.2	48

PKCELL
Green energy, easy life

SHENZHEN PKCELL BATTERY CO.,LTD

Company addrss:E2 Building,Guangming Technology Park,No.24 Zhonghua Road,Longhua New Area,Shenzhen

Tel: 86-755-33225299/86670672(switchboard)
Fax: 86-755-86670609
Company website: www.pkcell.com
For retailing: www.pkcellshop.com
E-mail: pkcell@pkcell.com

Factory address: Yongzhou city, Hunan Province
Tel: 86-746-8331678/8333170
Fax: 86-746-8331700

Ni-Cd Consumer Rechangeable Battery



Type	Model	Dimension (max)		Capacity	Norminal	Standard Charge		Rapid Charge		Reference Weight
		Diameter (mm)	Height (mm)	(mAH)	Voltage(V)	Current (mA)	Time (H)	Current (mA)	Time (H)	
AA	AA1100	14.5	50.5	1100	1.2	110	15	550	2.5	25
	AA1000			1000	1.2	100	15	500	2.5	24
	AA900			900	1.2	90	15	900	1.5	23
	AA800			800	1.2	80	15	800	1.5	21
	AA700			700	1.2	70	15	700	1.5	20
	AA600			600	1.2	60	15	600	1.5	19
	AA500			500	1.2	50	15	500	1.5	19
AAA	AAA380	10.5	44.5	380	1.2	38	15	380	1.5	13
	AAA350			350	1.2	35	15	350	1.5	12
	AAA300			300	1.2	30	15	300	1.5	11
C	C2500	25.8	51	2500	1.2	250	15	2500	1.5	70
D	D4000	33	61.5	4000	1.2	400	15	4000	1.5	140
	D4500			4500	1.2	450	15	4500	1.5	140
9V	9V120	17.5(T)*26.5(W)*48.5(H)		120	9V	12	15	120	1.5	42

Ni-Cd Industrial Rechargeable Battery



Type	Model	Size	Dimension (max)		Capacity	Norminal	Standard Charge		Rapid Charge		Reference Weight
			Diameter (mm)	Height (mm)	(mAH)	Voltage(V)	Current (mA)	Time (H)	Current (mA)	Time (H)	
AAA	1/3AAA80	1/3AAA	10.5	15.5	80	1.2	8	15	80	1.5	3
	2/3AAA200	2/3AAA	10.5	29	200	1.2	20	15	200	1.5	7
	AAA300A/B	AAA	10.5	44.5/43	300	1.2	30	15	300	1.5	11
	AAA400A	AAA	10.5	44.5	400	1.2	40	15	400	1.5	14
AA	1/3AA180	1/3AA	14.5	17	180	1.2	18	15	180	1.5	9
	2/3AA300	2/3AA	14.5	29	300	1.2	30	15	300	1.5	11
	2/3AA400	2/3AA	14.5	29	400	1.2	40	15	400	1.5	12
	4/5AA700	4/5AA	14.5	43.3	700	1.2	70	15	700	1.5	20
	AA500	AA	14.5	50.5	500	1.2	50	15	500	1.5	18
	AA600A/B	AA	14.5	50.5/49	600	1.2	60	15	600	1.5	19
	AA700A/B	AA	14.5	50.5/49	700	1.2	70	15	700	1.5	20
	AA800A/B	AA	14.5	50.5/49	800	1.2	80	15	800	1.5	21
	AA900A	AA	14.5	50.5	900	1.2	90	15	900	1.5	23
	AA900H	AA	14.5	51.4	900	1.2	90	15			23
	AA1000A/B	AA	14.5	50.5/49	1000	1.2	100	15	500	2.5	24
	4/3AA1100	4/3AA	14.5	65.5	1100	1.2	110	15	1100	1.5	30
A	1/3A240	1/3A	17	17	240	1.2	24	15	240	1.5	10
	2/3A600	2/3A	17	29	600	1.2	60	15	600	1.5	25
	4/5A1200	4/5A	17	40	1200	1.2	120	15	1200	1.5	28
	A1400	A	17	50	1400	1.2	140	15	1400	1.5	32
	4/3A1600	4/3A	17	66.5	1600	1.2	160	15	1600	1.5	41
SC	2/3SC600	2/3SC	23	26.5	600	1.2	60	15	600	1.5	25
	4/5SC1000	4/5SC	23	34	1000	1.2	100	15	1000	1.5	37
	SC1700P	SC	23	43	1700	1.2	170	15	1700	1.5	49
	SC1900P	SC	23	43	1900	1.2	190	15	1900	1.5	50
	SC1800	SC	23	43	1800	1.2	180	15	1800	1.5	49
	SC2000	SC	23	43	2000	1.2	200	15	1000	2.5	50
	4/3SC2200	4/3SC	23	50	2200	1.2	220	15	1100	2.5	56
C	C2000A/B	C	25.8	51/50	2000	1.2	200	15	2000	1.5	65
	C2500A/B	C	25.8	51/50	2500	1.2	250	15	2500	1.5	70
	C2500H	C	25.8	51	2500	1.2	250	15			70
	C3000A	C	25.8	51	3000	1.2	300	15	1500	2.5	75
D	D4000A/B	D	33	61.5/60.5	4000	1.2	400	15	4000	1.5	135
	D4500A/B	D	33	61.5/60.5	4500	1.2	450	15	4500	1.5	140
	D5000A/B	D	33	61.5/60.5	5000	1.2	500	15	5000	1.5	145
	3/2D7000	3/2D	33	90.5	7000	1.2	700	15	3500	2.5	195
F	F9000	F	33	90.5	9000	1.2	900	15	4500	2.5	210
9V	9V100	9V	17.5(T)*26.5(W)*48.5(H)		100	1.2	10	15	100	1.5	42
	9V120	9V	17.5(T)*26.5(W)*48.5(H)		120	1.2	12	15	120	1.5	42

Charger

Proper charging of Nickel-Metal Hydride (NiMH) batteries is important to optimize performance in any product. PKCELL® offers a wide range of chargers to meet the needs of our customers in terms of special features and price.



> Fast Charger

8152

6 942449 581525

Charges:
1-4 × AA
1-4 × AAA

NI-MH
NI-CD

Fast as Over Night

LCD indication
CHARGE





8154

Charges:
1-4 × AA
1-4 × AAA

NI-MH
NI-CD





Includes:

6 942449 581549

Fast as Over Night

> Standard Charger

8126

6 942449 581266

Charges:
1-4 × AA
1-4 × AAA

NI-MH
NI-CD

Fast as Over Night

Includes:





8182

Charges:
1-4 × AA
1-4 × AAA
1-4 × C
1-4 × D
1-2 × 9V

NI-MH
NI-CD

Fast as Over Night

Includes:





8174

6 942449 581747

Charges:
1-4 × AA
1-4 × AAA

NI-MH
NI-CD

Fast as Over Night

Includes:



